



tesa® Permanent Hooks Metal Oval

Product Information



BNR 66610, 66611

Product Description

tesa® Permanent Hooks OVAL METAL are classic shaped hooks for lightweight objects. They are made of brushed stainless steel and equipped for permanent fixation.

Product Features

- Easy to mount without drilling, screws or nails
- Permanent fixation for light objects
- Usable on tiles, glass, wood, plastic and a variety of other smooth surfaces*
- High quality, brushed stainless steel
- Simplified handling

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|--------------|------|
| • Type of adhesive | acrylic | • Hook shape | Oval |
|--------------------|---------|--------------|------|

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-----------------------------|--|
| • Application temperature from | +15 °C | • Chemical Resistance | no |
| • Application temperature to | +35 °C | • Material | Stainless steel |
| • Applicationfield | Bathroom, Kitchen | • Residue-free removability | no |
| • Area of use | Indoor | • Reusable | no |
| • Batteries included | no | • Suitable surfaces | Tiles, Most plastics, Glass, Metal, Steel |
| • Batteries required | no | • Waterproof | no |



tesa[®] Permanent Hooks Metal Oval

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>