



# 51036 PV5



## Product Information

PET cloth Sleeve® for superior abrasion protection and enhanced flexibility

## Product Description

tesa® Spiralsleeve 51036 PV5 is a PET cloth Sleeve® coated with an acrylic adhesive for spiral application.

Color: Black

## Product Features

- High temperature resistance 150°C/3000h
- High flexibility
- Superior abrasion resistance
- Unique adhesive-to-adhesive closure system guarantees secure bonding without additional spot wraps

## Application Fields

tesa® Spiralsleeve 51036 PV5 is designed for the engine compartment, providing superior abrasion protection and flexibility.

It combines the well known spiral application of a tape with the flexibility of a tesa® Sleeve.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing          | PET cloth        | • Total thickness | 530 µm |
| • Type of adhesive | advanced acrylic |                   |        |

## Properties/Performance Values

- |                               |         |                               |        |
|-------------------------------|---------|-------------------------------|--------|
| • Noise damping (LV312)       | Class B | • Temperature resistance min. | -40 °C |
| • Temperature resistance max. | 150 °C  |                               |        |

## Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 3 N/cm |
|---------|--------|

## Additional Information

- Standard width: 35 mm
- Standard lengths: 15 m, 10 m
- Standard core diameter: 38 mm
- Additional dimensions on request

For latest information on this product please visit <http://l.tesa.com/?ip=51036>



# 51036

# PV5

## Product Information

### Additional Information

- Available as right- & left-hand version (35 mm)

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51036>