



tesafilm® Neon

Product Information

BNR 53930, 53931

Product Description

The tesafilm® marking film is writable and can be removed without a trace. It is available in neon-yellow and neon-pink, providing a high signal effect. The adhesive film is ideally suited for marking and writing at home and in the office. That way it helps with organizing things. Available as single roll 10m:19mm or incl. mini dispenser for free-hand usage

Product Features

- Can be removed without a trace from most smooth surfaces
- Repositionable
- Signal colors: available in neon-yellow and neon-pink
- Writable
- Available as single roll 10m:19mm or incl. mini dispenser for free-hand usage

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PP film | • Total thickness | 57 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|----------------|--|------------------|
| • Tensile strength | 48 N/cm | • Residue-free removability | no |
| • Adhesive strength | Light adhesion | • Reusable | no |
| • Ageing resistance (UV) | no | • Roll width max | 19 mm |
| • Applicationfield | Office, Home | • Serrated blade | _NULL |
| • Batteries included | no | • Solvent free | yes |
| • Batteries required | no | • Suitable for right and/or left handers | _NULL |
| • Ecofriendly packaging | _NULL | • Suitable surfaces | Paper, Cardboard |
| • Hand tearability | yes | • Tear resistance | yes |
| • Hazard material | no | • Transparency | low |
| • Low noise unwinding | no | • Unwind force | 2 N/cm |
| • Max roll length | 10 m | • Writable | yes |
| • Photocopy neutral | no | | |



tesafilm[®] Neon

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>