



# tesa® Powerstrips Waterproof Hooks S, Plastic White



## Product Information

BNR 59782

### Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Made from high quality plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bathtub etc.)
- Hooks reusable with tesa Powerstrips Waterproof Small

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

### Application Fields

How to apply:

1. Clean the surface with alcohol or silicone-free glass cleaner
2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation - wait for 10 seconds minimum
3. Apply the Powerstrip Waterproof Small strip on the surface - press for 5 seconds minimum
4. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
5. Let the hook slide down on the base plate until it is locked

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                       |                  |                 |                |
|-----------------------|------------------|-----------------|----------------|
| • Type of adhesive    | synthetic rubber | • Hook shape    | Rounded square |
| • Holding power up to | 1 Kg             | • Silicone free | yes            |



# tesa® Powerstrips Waterproof Hooks S, Plastic White

## Product Information

### Properties/Performance Values

• Application temperature from	+15 °C	• Ozone resistance	no
• Application temperature to	+35 °C	• Residue-free removability	yes
• Applicationfield	Bathroom	• Reusable	yes
• Area of use	Indoor	• Reusable with	Powerstrips Waterproof Small
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Chemical Resistance	no	• Temperature resistance	yes
• Hazard material	yes	• Temperature resistance max.	35 °C
• Humidity resistance	yes	• Temperature resistance min.	15 °C
• Material	PS (polystyrene)	• UV resistant	no
• Oil and grease resistance	no	• Waterproof	yes

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>