



# tesapack<sup>®</sup> Paper Ultra Strong ecoLogo<sup>®</sup>



## Product Information

BNR 56000

## Product Description

With the tesapack<sup>®</sup> PAPER ULTRA STRONG ecoLogo<sup>®</sup> new standards are set in the area of well-performing and more sustainable products. With very strong adhesion for applications up to 30 kg and made of sustainable paper, the tape is an impressive performer.

## Product Features

- tesa<sup>®</sup> self-adhesive reinforced paper packaging tape
- Paper from certified forests
- High-performing packaging tape
- Excellent adhesion and very potent initial tack (tamper evidence)
- Ideal for heavy-duty packaging applications up to 30 kg
- Product with sustainable content, by having a solvent-free coating process
- Recycle-friendly according to INGEDE
- Can be disposed with the carton in the wastepaper bin without endangering the cardboard recycling process

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                        |                   |        |
|--------------------|------------------------|-------------------|--------|
| • Backing          | Glasfiber filament re- | • Total thickness | 210 µm |
|                    | inforced paper         |                   |        |
| • Type of adhesive | synthetic rubber       |                   |        |

## Properties/Performance Values

- |                          |                    |                       |                  |
|--------------------------|--------------------|-----------------------|------------------|
| • Elongation at break    | 6 %                | • Low noise unwinding | yes              |
| • Tensile strength       | 125 N/cm           | • Solvent free        | yes              |
| • Adhesive strength      | Very high adhesion | • Suitable surfaces   | Cardboard, Paper |
| • Ageing resistance (UV) | no                 | • Tear resistance     | yes              |
| • Applicationfield       | Home, Office       | • Unwind force        | 1 N/cm           |
| • Hand tearability       | no                 |                       |                  |



# tesapack<sup>®</sup> Paper Ultra Strong ecoLogo<sup>®</sup>

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>