



tesa® 4445

Product Information



Repulpable Single-Sided Splicing Tape

Product Description

tesa® 4445 is a single-sided repulpable splicing tape without liner consisting of a flat-back paper and a modified water soluble acrylic adhesive.

Colour: Light Blue

Product Features

- High tack properties
- Good adhesion values on coated and uncoated paper
- Very high tensile strength
- Good repulpability over full pH-range (pH3 –pH9)
- Paper from well-managed certified forests and other controlled sources

Application Fields

tesa® 4445 is particularly suitable for:

- End tabbing applications
- General purpose applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing | flat paper | • Total thickness | 190 µm |
| • Type of adhesive | repulpable tackified acrylic | • Color | blue |
| • Type of liner | none | | |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|--------------------------------|-----------|
| • Elongation at break | 8 % | • Static shear resistance | good |
| • Tensile strength | 90 N/cm | • Tack | very good |
| • Shelf life time (packed) < 25°C | 12 months | • Tensile strength (crosswise) | 42 N/cm |

For latest information on this product please visit <http://l.tesa.com/?ip=04445>



tesa[®] 4445

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04445>