



tesapack[®] ultra strong crystal clear

Product Information

BNR 57805, 57803, 57831, 57807

Product Description

tesapack[®] crystal clear is a high quality packaging tape perfectly suited for gift wrapping. It is made of a highly transparent and extra strong PP tape.

Product Features

- Very strong PP backing
- Solvent-free adhesive with high UV-resistance
- Excellent transparency for neat packaging
- High sealing security
- Even, low-noise unwinding
- Suitable for use with all available tesapack[®] hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 60 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------------|--------------------|----------------------|-----------|
| • Tensile strength | 37 N/cm | • Reusable | no |
| • Adhesive strength | High adhesion | • Roll width max | 50 mm |
| • Ageing resistance (UV) | yes | • Serrated blade | _NULL |
| • Applicationfield | Office, Home | • Solvent free | yes |
| • Batteries included | no | • Spare part service | no |
| • Batteries required | no | • Suitable surfaces | Cardboard |
| • Hand tearability | no | • Tear resistance | yes |
| • Humidity resistance | no | • Tensibility | 150 % |
| • Low noise unwinding | yes | • Tension control | _NULL |
| • Material | PP (polypropylene) | • Transparency | very good |
| • Max roll length | 66 m | • Writable | no |
| • Residue-free removability | no | | |



tesapack[®] ultra strong crystal clear

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>