



# tesa® On & Off Flooring Tape Hook & Loop

## Product Information

BNR 56187, 56188

## Product Description

tesa® Flooring Tape Hook and Loop is especially suited for the removable fixation of fleece and felt-backed carpet even in damp rooms and with underfloor heating.

## Product Features

- Suitable for fleece- or felt-backed carpets
- For all hard, dry and clean surfaces
- Can also be used with underfloor heating and in damp rooms
- Allows easy replacement of carpets

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Type of adhesive synthetic rubber
- Total thickness 1000 µm

## Properties/Performance Values

- |                         |               |                             |   |
|-------------------------|---------------|-----------------------------|---|
| • Adhesive strength     | High adhesion | • Material                  | PP (polypropylene)  |
| • Applicationfield      | Home          | • Residue-free removability | no  |
| • Batteries included    | no            | • Solvent free              | yes   |
| • Batteries required    | no            | • Suitable surfaces         | Tiles, Brick, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Chemical Resistance   | no            |                             |   |
| • Ecofriendly packaging | no            |                             |   |
| • Humidity resistance   | no            |                             |   |
|                         |               | • Tear resistance           | yes   |
|                         |               | • Temperature resistance    | no  |



# tesa<sup>®</sup> On & Off Flooring Tape Hook & Loop

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>