

tesa® Powerstrips Transparent Large

Product Information

BNR 58810

Product Description

tesa Powerstrips Transparent Large are self-adhesive double-sided strips perfectly suited for the unobtrusive fixation of transparent objects.

Product Features

• Transparent for unobtrusive fixation * Maximum hold of up to 1 kg on smooth surfaces* * Removable without trace thanks to the Powerstrips® technology * Limited UV-resistance (e.g. seasonal decoration) *Not suitable for use on styrofoam, foamed material, surfaces with non-sticking coating, porous materials

Application Fields

How to apply - Step by step:

- 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Apply the tesa Powerstrips® Transparent DECO Large strip on the surface press for 5 seconds minimum
- 3. Fix object onto surface press for 5 seconds minimum
- 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| • | Type of adhesive | synthetic rubber | • | Holding power up to | 1 Kg |
|---|------------------------------|------------------|---|---------------------|-------|
| • | Total thickness | 650 μm | • | Hook shape | _NULL |
| • | Holding power of strip up to | 1 Kg | • | Silicone free | yes |



tesa® Powerstrips Transparent Large

Product Information

Properties/Performance Values

| • | Ageing resistance (UV) | yes | • | Ozone resistance | yes |
|---|------------------------------|------------------------|---|-----------------------------|-----------------------|
| • | Application temperature from | -15 °C | • | Residue-free removability | yes |
| • | Applicationfield | Kitchen, Living room, | • | Reusable | no |
| | | Children's room, | • | Reusable with | _NULL |
| | | Office, Hall, Bathroom | • | Solvent free | yes |
| • | Area of use | Indoor | • | Suitable surfaces | Even wood, Tiles, |
| • | Batteries included | no | | | Most plastics, Glass, |
| • | Batteries required | no | | | Acrylic glass, Steel, |
| • | Chemical Resistance | no | | | Metal |
| • | Hazard material | no | • | Temperature resistance max. | 35 °C |
| • | Humidity resistance | no | • | Temperature resistance min. | 5 °C |
| • | Material | _NULL | • | UV resistant | yes |
| • | Oil and grease resistance | no | • | Water resistance | no |
| | | | • | Waterproof | no |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

