

tesa® Aluminium Tape

Product Information



BNR 56223

Product Description

tesa® Aluminium tape is a special self-adhesive plumbers tape perfectly suited to quickly repair any metal surface, such as heating appliences or gutters.

Product Features

- · Suitable for protecting, covering, insulating and repairing
- * May also be used for roof and gutter repairs
- * Temperature resistant from -40°C to +160°C
- * Water-, oil- and grease-resistant
- * Age-resistant
- * High adhesive strength

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

 Backing 	aluminium foil	 Total thickness 	100 μm
-----------------------------	----------------	-------------------------------------	--------

Type of adhesive acrylic



tesa® Aluminium Tape

Product Information

· Residue-free removability

Properties/Performance Values

 Tensile strength 		15 N/cm	•	Reusable
•	Abrasion resistance	no	•	Spare part service
•	Adhesive strength	High adhesion	•	Suitable surfaces
•	Applicationfield	Home, Garden,	•	Temperature res
		Garage, Roof, Car,	•	Temperature res
		Ceiling	•	Temperature res
•	Area of use	In- and Outdoor	•	Tensibility
•	Batteries included	no	•	UV resistant
•	Batteries required	no	•	Waterproof
•	Humidity resistance	yes	•	Writable
•	Material	Aluminium		
•	Oil and grease resistance	yes		

no

•	Spare part service	no
•	Suitable surfaces	Glass, Metal, Steel
•	Temperature resistance	yes
•	Temperature resistance max.	160 °C
•	Temperature resistance min.	-40 °C
•	Tensibility	5 %
•	UV resistant	yes
•	Waterproof	yes
•	Writable	no

no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

