

tesa® Adjustable Adhesive Nail for Tiles & Metal 3kg



Product Information

BNR 77764

Product Description

Height adjustable adhesive nail for up to 3kg. Perfect for hanging and aligning objects like kitchen utensils on smooth and solid surfaces like tiles and metal.

Product Features

- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per nail or 6kg using 2 nails
- · Height adjustable for straight alignment of objects
- · Removable without a trace
- · Reusable with a new strip

Application Fields

How to apply - Step by Step

- 1. To ensure the best possible bond, clean the surface with a silicone-freewindow cleaner or methylated spirit. The surface should be completely dry before application.
- 2. The Adhesive Strip should be applied to the rougher surface.
- 3. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil. Be careful not to touch the exposed adhesive area.
- 4. Now apply your tesa® Adhesive Nail by aligning it with the top edge of the strip and then folding it down. Press down evenly on the entire nail for at least 5 seconds.
- 5. The tab should be left accessible behind your object or beneath the nail for easy removal.
- 6. Push the red toggle up to unlock and adjust the nail head and then lock the head in place by pushing the red toggle back down until it clicks into place.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of adhesive synthetic rubber
Holding power up to 3 Kg
Holding power up to yes



tesa® Adjustable Adhesive Nail for Tiles & Metal 3kg

Product Information

Properties/Performance Values

•	Application temperature from	-15 °C	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Reusable with	Adhesive Strip 3kg
•	Batteries required	no			Tiles
•	Chemical Resistance	no	•	Solvent free	yes
•	Hazard material	no	•	Suitable surfaces	Even wood, Tiles,
•	Humidity resistance	no			Most plastics, Glass,
•	Material	PS (polystyrene)			Acrylic glass, Steel,
•	Oil and grease resistance	no			Metal
•	Ozone resistance	no	•	Temperature resistance max.	35 °C
			•	Temperature resistance min.	5 °C
			•	UV resistant	no
			•	Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

