



tesa[®] 4713 Paper Standard



Product Information

tesa[®] 4713 – Packaging Tape with Paper from Responsible Sources

Product Description

tesa[®] 4713 is a general-purpose packaging tape based on a fine crepe paper backing and a natural rubber adhesive. The paper backing of tesa[®] 4713 is made with paper from well-managed, certified forests and other controlled sources. The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Application Fields

- Sealing of cardboard boxes
- Suitable for light-weight packaging
- Good adhesion in recycled cardboards
- Brand showcase and advertisement purposes
- Suitable for manual and automatic dispensers
- Recycling-friendly tape according to INGEDE method 12

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------|----------------|-------------------|--------|
| • Supporto | Paper | • Spessore totale | 125 µm |
| • Massa adesiva | natural rubber | | |

Assortimento di prodotti

- | | |
|--------------------|-------|
| • Available colors | white |
|--------------------|-------|

Proprietà/Valori di prestazione

- | | | | |
|----------------------------|---------|------------------------|-----------|
| • Allungamento a rottura | 8 % | • Applicazione manuale | yes |
| • Resistenza alla trazione | 30 N/cm | • Strappabile a mano | very good |
| • Applicazione automatica | yes | | |

Adesione ai valori

- | | |
|------------------------|----------|
| • Adesività su Acciaio | 2.8 N/cm |
|------------------------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=04713>



tesa[®] 4713 Paper Standard

Product Information

Additional Information

tesa[®] 4713 is available in chamois (brown) and white.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04713>