



tesa[®] Powerstrips Self-Adhesive Cable Clip



Product Information

BNR 58035, 64364

Product Description

Use self-adhesive tesa Powerstrips Cable-Clips to run cables unobtrusively. They stick to just about any flat surface and come off easily to be reused anytime.

Product Features

- Easy to mount without drilling, screws or nails
- Easy to fix cables of up to 8mm diameter
- Removable without trace thanks to the Powerstrips technology
- Brings order where there is cable chaos
- Clip is reusable with tesa Powerstrip Small
- Cable-clip covers tesa Powerstrip completely

Application Fields

- How to apply - Step by step
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Small strip on the surface - press for 5 seconds minimum
 3. Open the cable clip and stick the back of the clip onto the strip - press for 5 seconds minimum
 4. Close and snap-lock the clip

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 1 Kg | • Silicone free | yes |



tesa[®] Powerstrips Self-Adhesive Cable Clip

Product Information

Properties/Performance Values

• Ageing resistance (UV)	yes	• Ozone resistance	yes
• Application temperature from	-15 °C	• Residue-free removability	yes
• Applicationfield	Kitchen, Living room, Children's room, Office, Hall, Bathroom	• Reusable	yes
• Area of use	Indoor	• Reusable with	Powerstrips Small
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Chemical Resistance	no	• Temperature resistance	yes
• Hazard material	no	• Temperature resistance max.	35 °C
• Humidity resistance	no	• Temperature resistance min.	5 °C
• Humidity sealing	no	• UV resistant	no
• Material	PS (polystyrene)	• Water resistance	no
• Oil and grease resistance	no	• Waterproof	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>