

51786 Detect Plus

Product Information

Double-sided splicing tape

Product Description

tesa® 51786 EasySplice® Detect Plus is a double-sided integrated flying splice tape consisting of an aluminised flat-back paper and an acrylic adhesive.

tesa® 51786 EasySplice® Detect Plus features especially

- Very high tack properties
- Very high shear resistance
- Extremely good heat resistance
- · Best adhesion on coated and uncoated paper
- Low splice thickness
- Reliable detection of splice position
- Smooth and easy application due to a flexible backing

The innovative tape composition includes the following functions:

- Slit liner for the secure fixation of the top sheet
- Aluminised backing for a reliable detection of the splice position
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Available with one or two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the printing process
- White paper backing for a fully printable splice due to an internal aluminisation

Colour: Orange

Product Features

- Very high tack properties
- Very high shear resistance
- Extremely good heat resistance
- · Best adhesion on coated and uncoated paper
- Low splice thickness
- Reliable detection of splice position
- Smooth and easy application due to a flexible backing
- Available with one or two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the printing process
- Slit liner for the secure fixation of the top sheet is included
- Aluminised backing for a reliable detection of the splice position is included
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Recycling-friendly premium splicing tape according to INGEDE 12 Method

Applications

tesa® 51786 EasySplice® Detect Plus is particularly suitable for:

For latest information on this product please visit http://l.tesa.com/?ip=51786





51786 Detect Plus

Product Information

Applications

• Flying splices in web printing industry

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

•	Backing Total thickness	Aluminised paper 110 µm	•	Color	orange/silver
Properties/Performance Values					
٠	Elongation at break	6%	٠	Shelf life time (packed) < 25°C	12 months
٠	Tensile strength	36 N/cm			

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 - as of 17/02/24 - en-AU