



# tesa<sup>®</sup> 4282 PV1

## Product Information

Carton sealing tape

### Product Description

tesa<sup>®</sup> 4280 is a self-adhesive tape based on a 28µm PP film and a synthetic rubber adhesive. The tape is ideal for sealing and packaging light- to medium-weight cartons. The packing tape features easy unwinding, is suitable for manual application and is compatible with any handheld dispenser. The carton sealing tape features a short dwell time before reaching its final adhesive strength and is very tacky, allowing for fast and precise positioning during application.  
tesa<sup>®</sup> 4282 displays its best performance when applied at moderate temperatures and indoors. The packing tape has excellent adhesive properties on both polar and non-polar surfaces.

### Product Features

- The packing tape features easy unwinding, is suitable for manual application, and is compatible with any handheld dispenser.
- The carton sealing tape features a short dwell time before reaching final adhesion power and is very tacky, allowing for fast and precise positioning during application.
- The packing tape shows excellent adhesive properties on both polar and non-polar surfaces.

### Applications

- tesa<sup>®</sup> 4282 is a multi-purpose carton sealing and packaging tape, ideal for light- to medium-weight cartons.
- The packing tape can be used either manually or with automatic sealing equipment.
- The tape features easy unwinding and good adhesion to a wide range of surfaces.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Applications

- |                    |                  |                   |       |
|--------------------|------------------|-------------------|-------|
| • Backing          | PP film          | • Total thickness | 45 µm |
| • Type of adhesive | synthetic rubber |                   |       |

### Properties/Performance Values

- |                       |         |                         |     |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 145 %   | • Automatic application | yes |
| • Tensile strength    | 43 N/cm |                         |     |

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 5 N/cm |
|---------|--------|



# tesa<sup>®</sup> 4282 PV1

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04282>