



# 73524 FE-X (EA)



## Product Information

Foam plate mounting tape: FLEX Product Design

## Product Description

Double-sided foam tape

### Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

### Adhesive properties

- Low tack surface characteristics
- Best plate bonding
- Easy plate demounting
- Excellent tape bonding towards sleeve side

### Additional properties

- Structured PP-liner to prevent formation of air pockets when the plate is mounted
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves

## Product Features

- Foam properties: Low thickness tolerance. Long lasting, constant recovery characteristics
- Adhesive properties: Low tack surface characteristics. Best plate bonding. Easy plate demounting. Excellent tape bonding towards sleeve side.
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves.

## Applications

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Applications

• Backing	PE foam with film lamination	• Type of liner	PP
• Type of adhesive	tackified acrylic	• Total thickness	550 µm

For latest information on this product please visit <http://l.tesa.com/?ip=73524>



# 73524 FE-X (EA)

## Product Information

### Properties/Performance Values

- Color of foam purple
- Hardness medium
- Thickness category 500

### Additional Information

Available liner options:

- PV0: White embossed PP-liner
- PV21: Transparent structured easy application (EA) PET liner for excellent air removal during plate and tape mounting

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=73524>