



tesa® 51006

Product Information



PET cloth tape for abrasion protection

Product Description

tesa® 51006 is a PET cloth wire harness tape with a rubber based adhesive.

Major Features:

- High temperature resistance 150°C/3000h
- Abrasion resistant
- Strong adhesion

Color: Black

Product Features

- Resistant to abrasion
- High initial tack and adhesion
- Optimized for manual application
- Flag-resistant
- Can withstand environmental influences
- Constant unwind force – optimized for manual application
- Aging-resistant
- Flame-retardant
- Flexible and smooth

Applications

tesa® 51006 is designed for the engine compartment, providing abrasion protection.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing | PET cloth | • Total thickness | 320 µm |
| • Type of adhesive | rubber based | | |

Properties/Performance Values

- | | | | |
|-------------------------------|----------|-----------------------------------|----------------------|
| • Elongation at break | 22 % | • Temperature resistance min. | -40 °C |
| • Tensile strength | 175 N/cm | • Unwind force (roll width < 9mm) | 10 N/roll (30 m/min) |
| • Noise damping (LV312) | Class A | • Unwind force (roll width > 9mm) | 10 N/roll (30 m/min) |
| • Temperature resistance max. | 150 °C | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51006>



tesa[®] 51006

Product Information

Adhesion to Values

- Steel 4.5 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm
- Applicable for red ring assembly aid

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51006>