



tesa[®] 7476

Product Information



tesa[®] 7476

Product Description

tesa[®] 7476 has been successfully deployed for many years when it comes to assessing the release properties of silicone coatings (Finat 10 or similar).

For a comprehensive characterization of release properties it is recommended to use both tesa[®] 7475 (acrylic adhesive) and tesa[®] 7476 (natural rubber adhesive).

It is recommended to store tesa[®] 7476 at 23 °C and 50 % relative humidity.

Product Features

tesa[®] 7476 has been successfully deployed for many years when it comes to assessing the release properties of silicone coatings (Finat 10 or similar).

For a comprehensive characterization of release properties it is recommended to use both tesa[®] 7475 (acrylic adhesive) and tesa[®] 7476 (natural rubber adhesive).

It is recommended to store tesa[®] 7476 at 23 °C and 50 % relative humidity.

Application Fields

Characterization of silicone coatings

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Backing material Grid cotton cloth, cotton fabric
- Type of adhesive Grid natural rubber
- Type of liner Grid glassine

Properties/Performance Values

- Shelf life time 12 months



tesa[®] 7476

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07476>