

# tesa® 4150

# **Product Information**



# Masking tape

# **Product Description**

tesa® 4150 is a masking tape with a PVC-backing and age-resistant acrylic adhesive.

#### **Product Features**

tesa® 4150 is a masking tape with a PVC-backing and age-resistant acrylic adhesive.

## **Application Fields**

- · Masking during chrome-plating
- Masking during etching e.g. to decorate surfaces of glass or metal
- Masking during anodising e.g. galvanising aluminium surfaces
- · Masking during multi-colour painting

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing material	PVC film	•	Total thickness	70 μm
•	Type of adhesive	acrylic			

# **Properties/Performance Values**

•	Elongation at break	70 %	•	Easy to remove	yes
•	Tensile strength	53 N/cm			

### Adhesion to Values

steel	4 N/cm



tesa® 4150

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

