



tesa[®] 4338

Product Information



High Performance Masking Tape Grade - up to 120 °C / 248 F

Product Description

tesa[®] 4338 is a green coloured smooth masking tape for highly demanding paint masking applications, especially in transportation sectors such as marine, train, truck and various others where high conformability and clean paint edges are required.

The age resistant natural rubber adhesive has a high initial tack, provides outdoor usability for up to 14 days*, temperature resistance up to 120 °C / 248 F and clean removal.

*14 day UV resistance in Central and Northern Europe.

Sustainable Aspects

54% bio-based content in total product excluding liner (by weight)



Product Features

- The aging resistant natural rubber adhesive has a good quick stick, provides outdoor usability for up to seven-days, temperature resistance up to 120 °C / 248 F and clean removal.

Application Fields

- High visibility due to vivid colour
- Excellent handling (easy and controlled unwinding, finger friendly, and high conformability)
- For multiple drying cycles – up to six cycles at 120 °C/40 min
- Excellent adherence of paints and fillers
- Good initial tack for secure fixation of masks without peel-off
- Clean paint edges
- 14 day UV resistance for short outdoor storing of masked objects

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

For latest information on this product please visit <http://l.tesa.com/?ip=04338>



tesa[®] 4338

Product Information

Product Construction

| | | | |
|--------------------|-----------------------|-------------------|--|
| • Backing material | slightly-creped paper | • 54 | Bio-based content of liner by weight (acc. EN 16785) |
| • Type of adhesive | natural rubber | | 145 µm |
| | | • Total thickness | |

Properties/Performance Values

| | | | |
|-----------------------|---------|--------------------|-----------|
| • Elongation at break | 13 % | • Easy to remove | yes |
| • Tensile strength | 43 N/cm | • Hand tearability | very good |

Adhesion to Values

| | |
|---------|----------|
| • steel | 3.5 N/cm |
|---------|----------|

Additional Information

Masking during spray painting with oven drying up to 120°C.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04338>