

tesa® extra Power Universal

Product Information



BNR 56348, 56338, 56389, 56388, 56380, 56490, 56396

Product Description

tesa® extra Power Universal is a versatile duct tape with high bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- · Very good adhesion to all types of surfaces
- · Weather-resistant for in-and outdoor applications
- · Tearable by hand
- Solvent-free

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PE-film with PET-	•	Total thickness	215 μm
		filament			
•	Type of adhesive	synthetic rubber			

Properties/Performance Values

 Tensile strength Adhesive strength Ageing resistance (UV) Application temperature from Application temperature to Applicationfield 	100 N/cm High adhesion yes +10 °C +50 °C Garden, Garage, Car, Home Outdoor	 Ozone resistance Residue free removal Reusable Solvent free Spare part service Suitable surfaces 	yes no no yes no Even wood, Tiles, Most plastics, Glass, Metal
 Batteries included Batteries required Ecofriendly packaging Hand tearability Hazard material Humidity resistance Material Oil and grease resistance 	no no no yes no yes PE (polyethylene) yes	 Tear resistance Temperature resistance Temperature resistance max. Tensibility UV-resistant Water resistance Waterproof Writable 	yes yes 95°C 19% yes yes yes no



tesa® extra Power Universal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

