



tesa[®] Ceiling hook for wallpaper and plaster 0.5kg

Product Information

BNR 77781

Product Description

To attach decoration such as a mobile without drilling, the ceiling hook for wallpaper & plaster with its revolving hook head is the right choice. It's easy to attach and take off without a trace. To attach decoration such as a mobile without drilling, the ceiling hook for wallpaper & plaster with its revolving hook head is the right choice. It's easy to attach and take off without a trace.

Product Features

- Ceiling hook for sensitive surfaces (wallpaper & plaster)
- Mounting baby mobiles and other decorative items without drilling
- Holds objects of up to 0.5kg
- Easy On & Off: no tools, removable without a trace
- Reusable with new adhesive strip
- Ceiling hook for sensitive surfaces (wallpaper & plaster)
- Mounting baby mobiles and other decorative items without drilling
- Holds objects of up to 0.5kg
- Easy On & Off: no tools, removable without a trace
- Reusable with new adhesive strip

Application Fields

||

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------------------|------------------|-----------------------|--------|
| • Type of adhesive | synthetic rubber | • Holding power up to | 0.5 Kg |
| • Holding power of strip up to | 0.5 Kg | • Hook shape | Round |
| • Holding power of tape up to | 0.5 | • Silicone free | yes |



tesa[®] Ceiling hook for wallpaper and plaster 0.5kg

Product Information

Properties/Performance Values

• Application temperature from	-15 °C	• Residue free removal	yes
• Area of use	Indoor	• Reusable	yes
• Batteries included	no	• Reusable with	_NULL
• Batteries required	no	• Solvent free	yes
• Chemical resistance	no	• Suitable surfaces	Plaster, Wallpaper
• Hazard material	no	• Temperature resistance max.	35 °C
• Humidity resistance	no	• Temperature resistance min.	5 °C
• Material	PS (polystyrene)	• UV-resistant	no
• Oil and grease resistance	no	• Waterproof	no
• Ozone resistance	no		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>