

# tesa® Powerbond OUTDOOR

## **Product Information**



BNR 55750, 55764, 64351, 55751, 55756

### **Product Description**

tesa® Powerbond OUTDOOR is a strong weather resistant double-sided self-adhesive tape suitable for a wide range of outdoor applications.

#### **Product Features**

- · Ideal for exterior use
- · UV, water and temperature-resistant
- Holds up to 1 kg\* per 10cm tape
- · Holds on tiles, brick, stone, metal and most plastics

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Backing material	Acrylic	•	lotal thickness	1140 µm
•	Type of adhesive	acrylic	•	Holding power of tape up to	10 KG/M

#### **Properties/Performance Values**

•	Ageing resistance (UV)	yes	•	Material	_NULL
•	Application temperature	from -80°C up to -10°C	•	Residue free removal	no
•	Application temperature from	-10 °C	•	Reusable	no
•	Applicationfield	Garden, Garage,	•	Suitable surfaces	Tiles, Most plastics,
		Home			Glass, Metal, Steel
•	Area of use	Outdoor	•	Temperature resistance max.	80 °C
•	Batteries included	no	•	Temperature resistance min.	15 °C
•	Batteries required	no	•	UV-resistant	yes
•	Chemical resistance	no	•	Waterproof	yes
•	Hazard material	no			

<sup>\*</sup>For flat objects up to 10mm thick and on most smooth, sufficiently firm surfaces



# tesa® Powerbond OUTDOOR

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

