



tesamoll[®] Door-to-floor double-roll

Product Information

BNR 05418

Product Description

The tesamoll[®] Door-to-Floor Double Roll is a non-adhesive and removable instant draught excluder for doors that is able to seal gaps of up to 22 mm.

Product Features

- Suitable for smooth flooring surfaces like parquet, wooden or tile floors without a (or just with a very low) doorsill
- Suitable for interior use
- Suitable for gaps of up to 22mm
- Suitable for door leaf thicknesses up to 40 mm
- No adhesive

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Type of adhesive none
- Gap coverage up to 22 mm

Properties/Performance Values

- Applicationfield Home, Door
- Batteries included no
- Batteries required no
- Chemical resistance no
- Material Polyester, PE (polyethylene), LDPE (Low-density polyethylene)
- Residue free removal yes
- Reusable yes
- Solvent free yes
- Suitable surfaces Wooden floors



tesamoll[®] Door-to-floor double-roll

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>