



tesamoll® P-Profile

Product Information

BNR 55703, 05391, 05395, 05390

Product Description

tesamoll® P-Profile is a self-adhesive window seal made for insulating windows. It is a durable draught excluder able to seal even larger gaps in older windows.

Product Features

- Saves up to 35% of energy costs
- Self-adhesive, long-lasting rubber P-Profile
- Seals all gaps from 2 to 5mm
- Durability: 8 years
- Weather- UV- and ozone-resistant
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Easy to remove
- Temperature-resistant from -50°C to +60°C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|---------------------------------|------|
| • Backing material | EPDM rubber foam | • Energy saving potential up to | 35 % |
| • Type of adhesive | synthetic rubber | • Gap coverage up to | 5 mm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-------------------|
| • Applicationfield | Home | • Material | Synthetic, Fabric |
| • Batteries included | no | • Residue free removal | no |
| • Batteries required | no | • Solvent free | yes |
| • Chemical resistance | no | • Temperature resistance | yes |
| • Durability | 8 years | • Temperature resistance max. | 60 °C |
| • Humidity resistance | yes | • Temperature resistance min. | -20 °C |



tesamoll[®] P-Profile

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>