

52022 Steel Master

Product Information



Product Description

tesa® 52022 Softprint Steel Master is a double-coated foam tape, designed specifically for mounting thicker photopolymer plates of thickness 1.70mm (0.067"), 2.54mm (0.1002) and above in wide-web film and paper flexographic printing, on machines using steel cylinders or sleeves.

The soft foam makes this the ideal solution for screen printing with some combination work.

Foam properties:

- · Highly compressible foam, with superior recovery for excellent print quality
- · Long lasting recovery characteristics for extended and high speed print runs
- · Low thickness tolerances for quick print preparation and reduced waste

Adhesive properties:

- · High bonding on open side to steel cylinder or sleeve to avoid plate movement
- High bonding to plate to avoid edge lifting or plate movement
- Non increasing bonding power for easy repositioning and especially for easy demounting of plate and tape
- Very cohesive adhesive structure for demounting without adhesive residues

Additional properties:

- The structured PP-liner prevents the formation of air pockets when plate mounting
- Red colour marking indicates the soft foam

Application Fields

tesa $^{\circ}$ 52022 Softprint Steel Master is a 500 μ m (20 mil) category double-coated foam tape, designed specifically for mounting thicker photopolymer plates of thickness 1.70mm (0.067"), 2.54mm (0.100";) and above in wide-web film and paper flexographic printing, on machines using steel cylinders or sleeves.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing material
Type of liner
Type of adhesive
Type of liner

Properties/Performance Values

Hardness soft
Thickness category
500



52022 Steel Master

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

