



tesa[®] 4613 Utility Duct Tape



Product Information

Utility grade duct tape

Product Description

tesa[®] 4613 is a utility grade duct tape. It consists of a 27 mesh woven PET/cotton fabric backing coated with a natural rubber adhesive.

tesa[®] duct 4613 is a self adhesive tape with typical duct features for a wide range of applications.

Features:

- good adhesion even on rough surfaces
- easy to tear by hand
- water repellent
- flexible
- available in 2 colors: black, silver

Product Features

- It comprises a natural-rubber adhesive mass and can be torn by hand.
- The duct tape is also suited to rough surfaces and is waterproof.

Application Fields

- Sealing of ducts
- Fastening of protection films
- Sealing of rubbish bags
- Fixing, closing, packaging and a lot more!

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|-------------------|--------|
| • Backing | PE laminated cloth | • Total thickness | 180 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|-------------------------------------|--------------------------|
| • Elongation at break | 18 % | • Hand tearability | good |
| • Tensile strength | 30 N/cm | • Humidity resistance | good |
| • Ageing resistance (UV) | good | • Mesh | 27 count per square inch |
| • Fluorescent | no | | |
| • Fogging | low | • Temperature resistance short term | 80 °C |

For latest information on this product please visit <http://l.tesa.com/?ip=04613>



tesa[®] 4613 Utility Duct Tape

Product Information

Adhesion to Values

- Steel 4.3 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04613>