

tesa® 50533 Edge Securing DISCONTINUED



Product Information

High adhesion temporary protection tape for freshly painted surfaces

Product Description

tesa® Edge Securing 50533 consists of an UV-stabilized backing coated with a high adhesion EVA adhesive. Features & benefits:

- Paint protection during outdoor storage up to 12 months
- Secure adhesion during transport
- Easy disposal both the film and the adhesive system are environmentally friendly

Product Features

- Reliable paint protection during outdoor storage for up to 12 months
- Secure high adhesion during transport
- Suitable for die cutting and printing
- Thick material quality for high protection
- Easy to apply and remove
- Easy disposal both the film and the adhesive system are environmentally friendly
- It consists of a UV-stabilized backing coated with a high adhesion EVA adhesive.

Application Fields

- tesa® Edge Securing 50533 ensures high-strength adhesion and can be used to keep tesa Bodyguard® tapes securely in place, especially in areas of difficult geometries to prevent dust and humidity penentration
- tesa[®] Edge Securing 50533 is suitable for die-cutting and can be printed on to be used as security, steering or marking label
- tesa[®] Edge Securing 50533 can also be used as base material for heavy duty protection pads for bumpers and door edges

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

BackingType of adhe	esive	polyolefinic film EVA	•	Total thickness	96 µm
Properties/Performance Values					
Elongation a	it break	660 %	•	Easy to remove	yes
Tensile strer	igth	21.5 N/cm	•	Suitable for die cutting	yes
Chemical Re	esistance	very good			



tesa® 50533 Edge Securing DISCONTINUED

Product Information

Adhesion to Values

Steel

3 N/cm

Additional Information

tesa® Edge Securing 50533 is also available as die cut product solution as tesa® Edge Securing 54533.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 25/02/24 – en-SG