

tesa® 51316

Product Information

Medium grade bandoliering tape

Product Description

tesa® 51316 is a medium grade paper tape designed for bandoliering/sequencing of axial leaded components such as capacitors, resistors, and diodes.

Product Features

- Natural rubber adhesive for good belting performance
- Temperature resistance up to 100°C
- · Thin backing for good conformability

Application Fields

- Stock-belting of axial leaded components
- Sequencing of axial leaded components

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	slightly-creped paper	•	Total thickness	140 μm
•	Type of adhesive	natural rubber			

Properties/Performance Values

Elongation at break
Tensile strength
38 N/cm

Adhesion to Values

• Steel 3.4 N/cm



tesa® 51316

Product Information

Additional Information

Colour: chamois

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

