



# tesa<sup>®</sup> 4289

## Product Information



Heavy duty tensilised strapping tape

### Product Description

tesa<sup>®</sup> 4289 is a heavy duty tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa<sup>®</sup> 4289 features very high tensile strength with low elongation at the same time. The product is highly abrasion resistant.

### Product Features

- tesa<sup>®</sup> 4289 features very high tensile strength with low elongation at the same time.
- The product is highly abrasion resistant.

### Application Fields

Surface protection of glass, bundling of heavy steel pipes, palletising, end tabbing of light gauge rolled steel and finished metals.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | MOPP           | • Total thickness | 144 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                       |          |                             |     |
|-----------------------|----------|-----------------------------|-----|
| • Elongation at break | 35 %     | • No discoloration          | yes |
| • Tensile strength    | 420 N/cm | • Residue-free removability | yes |

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 5 N/cm |
|---------|--------|



# tesa<sup>®</sup> 4289

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04289>