

tesa®, tesa® Professional 65538PRO Anti-slip Black/Yellow



Product Information

Anti Slip safety solution

Product Description

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip yellow & black is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application.

Product Features

- The strong adhesive mass of acrylate ensures safe footing on the underlying surface.
- · The particularly abrasion-resistant and resilient adhesive tape is impervious to chemicals and salt water
- It can be torn by hand and removed again without any difficulties.
- It is certified in accordance with DIN 51130
- · The anti slip effect lasts for up to two years with ordinary use.

Application Fields

Everywhere safe footing is required.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PVC film coated with	•	Color of liner	yellow
		mineral particles	•	Thickness of liner	180 µm
•	Type of adhesive	acrylic	•	Thickness of tape	720 μm
•	Total thickness	900 μm			

Properties/Performance Values

 Elon 	gation at break	25 %	•	Easy to write on	no
 Tens 	ile strength	30 N/cm	•	Fluorescent	no
 Abra 	ision resistance	very good	•	Hand tearability	good
 Age 	ng resistance (UV)	good	•	Humidity resistance	very good
• Batte	eries included	no	•	Softener resistance	good
• Batte	eries required	no	•	Suitable for die cutting	yes
• Che	mical Resistance	good	•	Temperature resistance long	50 °C
 Easy 	to remove	no		term	
			•	Water resistance	good



tesa®, tesa® Professional 65538PRO Anti-slip Black/Yellow

Product Information

Adhesion to Values

• Steel 5.8 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

