



# tesa® 4328

## Product Information



High quality general purpose paper masking tape in colors

### Product Description

tesa® 4328 is a finely creped paper masking tape with a natural rubber adhesive.  
tesa® 4328 can be used on various surfaces; including painted metal, rubber, glass and chromed parts.

### Sustainable Aspects

48% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

### Product Features

- The products' natural rubber adhesive offers high tack and excellent adhesion on a variety of surfaces.
- It can withstand high temperatures making it suitable for oven-drying.

### Application Fields

The product is recommended for bundling, bag sealing, marking and general purpose masking applications.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |  |                    |
|--------------------|-----------------------|--|--------------------|
| • Backing          | slightly-creped paper | • Bio-based content of liner by weight (acc. EN 16785) | 48 %               |
| • Type of adhesive | natural rubber        | • Total thickness                                      | 175 µm<br>6.9 mils |

### Properties/Performance Values

- |                       |                      |                    |           |
|-----------------------|----------------------|--------------------|-----------|
| • Elongation at break | 12 %                 | • Easy to remove   | yes       |
| • Tensile strength    | 42 N/cm<br>24 lbs/in | • Hand tearability | very good |

### Adhesion to Values

- |         |                        |
|---------|------------------------|
| • Steel | 4.8 N/cm<br>43.9 oz/in |
|---------|------------------------|

For latest information on this product please visit <http://l.tesa.com/?ip=04328>



# tesa<sup>®</sup> 4328

## Product Information

### Additional Information

tesa<sup>®</sup> 4328 is suitable for masking during paint spraying with oven drying (up to 80 °C/176°F). After the oven drying process tesa<sup>®</sup> 4328 can be easily removed without tearing and without leaving any residues. The product is easily tearable by hand.

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04328>