



tesa[®] 53021 PV10

Product Information

tesa[®] 53021US Standard Bag Sequencing Tape

Product Description

tesa[®] 53021 is a high performing bag sequencing tape with a tensilized polypropylene backing and rubber adhesive specially designed for bag sequencing applications. This adhesive system provides a secure bond while removing cleanly from various surfaces without adhesive residue or delamination. The mono-oriented polypropylene backing exhibits high tensile strength and low elongation.

Product Features

- solvent-free adhesive
- low elongation
- high tensile strength

Application Fields

- Sequencing of bags for the poultry, meat, dairy, and other related industries
- Medium-high peel adhesion

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------------------|
| • Backing | TPP | • Total thickness | 150 µm |
| • Type of adhesive | synthetic rubber | • Color | 5.9 mils
white |

Properties/Performance Values

- | | | | |
|-----------------------|--------------------------|----------------|-----|
| • Elongation at break | 35 % | • Solvent free | yes |
| • Tensile strength | 350 N/cm
199.9 lbs/in | | |

Adhesion to Values

- | | |
|---------|------------------------|
| • Steel | 6.5 N/cm
59.4 oz/in |
|---------|------------------------|



tesa[®] 53021 PV10

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53021>