



# tesa® 4092 PV10



## Product Information

tesa® 4092US Standard Strapping Tape

## Product Description

tesa® 4092 is a utility grade strapping tape with tensilized polypropylene backing and rubber adhesive to provide good initial tack. The mono-oriented polypropylene backing exhibits high conformability, good tensile strength, and low elongation. With effortless dispensing, our tape accommodates both manual and automatic operations.

## Product Features

- solvent-free adhesive
- low elongation
- good workability

## Application Fields

- Medium duty bundling of pipes (i.e., copper, iron and plastic)
- Temporary fixation
- Medium-duty palletizing & reinforcing
- “L/C” clipping

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing          | TPP              | • Total thickness | 105 µm |
| • Type of adhesive | synthetic rubber | • Color           | black  |

## Properties/Performance Values

- |                       |                          |                             |     |
|-----------------------|--------------------------|-----------------------------|-----|
| • Elongation at break | 35 %                     | • No discoloration          | yes |
| • Tensile strength    | 250 N/cm<br>142.8 lbs/in | • Residue-free removability | yes |

## Adhesion to Values

- |         |                        |
|---------|------------------------|
| • Steel | 7.5 N/cm<br>68.5 oz/in |
|---------|------------------------|

For latest information on this product please visit <http://l.tesa.com/?ip=04092>



# tesa<sup>®</sup> 4092 PV10

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04092>