



# tesa<sup>®</sup> extra Power Extreme Outdoor

## Product Information

BNR 56395

### Product Description

Use tesa<sup>®</sup> extra Power Extreme Outdoor for all situations calling for an extremely weather resistant and waterproof repairing tape with extra high adhesion.

### Product Features

- Extremely weather-resistant and waterproof, especially designed for outdoor applications
- 1 year UV-resistant (UV-treated PE film)
- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- Temperature-resistant from -40°C to +95°C
- Hand-tearable
- Solvent-free

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                   |                   |        |
|--------------------|-------------------|-------------------|--------|
| • Backing          | PE extruded cloth | • Total thickness | 210 µm |
| • Type of adhesive | synthetic rubber  |                   |        |



# tesa<sup>®</sup> extra Power Extreme Outdoor

## Product Information

### Properties/Performance Values

|                                |                              |                               |   |
|--------------------------------|------------------------------|-------------------------------|---|
| • Tensile strength             | 41 N/cm                      | • Residue-free removability   | no  |
| • Adhesive strength            | Very high adhesion           | • Reusable                    | no  |
| • Ageing resistance (UV)       | yes                          | • Solvent free                | yes   |
| • Application temperature from | +10 °C                       | • Spare part service          | no  |
| • Application temperature to   | +50 °C                       | • Suitable surfaces           | Even wood, Tiles,<br>Most plastics,<br>Glass, Acrylic glass,<br>Cardboard, Paper,<br>Metal, Steel |
| • Applicationfield             | Home, Garden, Car,<br>Garage |                               |   |
| • Area of use                  | Outdoor                      |                               |   |
| • Batteries included           | no                           | • Tear resistance             | yes   |
| • Batteries required           | no                           | • Temperature resistance      | yes   |
| • Ecofriendly packaging        | no                           | • Temperature resistance max. | 95 °C   |
| • Hand tearability             | yes                          | • Temperature resistance min. | -40 °C  |
| • Hazard material              | no                           | • Tensibility                 | 23 %  |
| • Humidity resistance          | yes                          | • Transparency                | medium  |
| • Material                     | PE (polyethylene)            | • UV resistant                | yes   |
| • Oil and grease resistance    | no                           | • Water resistance            | yes   |
| • Ozone resistance             | yes                          | • Waterproof                  | yes   |
|                                |                              | • Writable                    | no  |

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>