



# tesa® 60996

## Product Information



## Product Description

tesa® 60996 is a translucent, double-sided self-adhesive tape consisting of a non-woven backing and a tackified acrylic adhesive.

## Product Features

- Excellent wetting property on different kinds of foam, felt material
- Very good converting properties

## Application Fields

- Lamination of foam and felt

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |             |
|--------------------|-------------------|-------------------|-------------|
| • Backing          | non-woven         | • Total thickness | 130 µm      |
| • Type of adhesive | tackified acrylic | • Color           | translucent |
| • Type of liner    | PE-coated paper   | • Color of liner  | white       |

## Properties/Performance Values

- |        |           |
|--------|-----------|
| • Tack | very good |
|--------|-----------|

## Adhesion to Values

- |                             |           |                         |           |
|-----------------------------|-----------|-------------------------|-----------|
| • ABS (initial)             | 9.3 N/cm  | • PC (after 14 days)    | 13.7 N/cm |
| • ABS (after 14 days)       | 16 N/cm   | • PE (initial)          | 3.2 N/cm  |
| • Aluminium (initial)       | 8 N/cm    | • PE (after 14 days)    | 4.1 N/cm  |
| • Aluminium (after 14 days) | 16.3 N/cm | • PP (initial)          | 3.5 N/cm  |
| • Glass (initial)           | 9.3 N/cm  | • PP (after 14 days)    | 7 N/cm    |
| • Glass (after 14 days)     | 13.4 N/cm | • Steel (initial)       | 9 N/cm    |
| • PC (initial)              | 11 N/cm   | • Steel (after 14 days) | 14.1 N/cm |

## Additional Information

Liner variants:

PV43 white PE-coated paper liner / blue tesa logo

PV44 white PE-coated paper liner / non-printed

For latest information on this product please visit <http://l.tesa.com/?ip=60996>



# tesa<sup>®</sup> 60996

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60996>