

# 61445

## Product Information



Repulpable, black single-sided splicing tape

### Product Description

tesa® CaRes 61445 is a single-sided repulpable splicing tape, with a liner consisting of a flat-back paper and a modified water soluble acrylic adhesive.

### Product Features

- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO<sub>3</sub>)
- Black backing with high colour density for reliable optical detection
- Thin but strong backing to allow a low total splice thickness
- tesa® CaRes 61445 is certified by independent laboratories for: Repulpability according to TAPPI UM-213 over full pH-range (pH3 – pH9)
- Very high shear strength
- Printable and coatable backing for easy further processing
- Very high heat resistance
- Very good adhesion values on most paper grades
- Paper from well-managed certified forests and other controlled sources

### Application Fields

tesa® CaRes 61445 is particularly suitable for:

- Manual permanent butt-splicing
- Use in automatic butt-splice applicators

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                              |                   |       |
|--------------------|------------------------------|-------------------|-------|
| • Backing          | flat paper                   | • Total thickness | 80 µm |
| • Type of adhesive | repulpable tackified acrylic | • Color           | black |
| • Type of liner    | repulpable siliconised paper |                   |       |

### Properties/Performance Values

- |                                   |           |                                |         |
|-----------------------------------|-----------|--------------------------------|---------|
| • Elongation at break             | 6 %       | • Tack                         | medium  |
| • Shelf life time (packed) < 25°C | 12 months | • Tensile strength (crosswise) | 30 N/cm |
| • Static shear resistance         | very good |                                |         |

For latest information on this product please visit <http://l.tesa.com/?ip=61445>



# 61445

## Product Information

### Additional Information

Other products for butt-splicing:

- tesa® 51444 - reduced thickness for thinner splices
- tesa® 51445 - stronger backing for higher splice security
- tesa® 51455 - slit liner for easier manual splice application
- tesa® 51465 - slit liner and splitting strip for secure tape fixation during the manual splice preparation

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61445>