

tesa® Easy Cover Outdoor

Product Information

BNR 56589

Product Description

tesa® Easy Cover Outdoor is a convenient 2 in 1 solution with cloth tape and masking foil. It is specifically customised for using in the outdoor areas. Especially during plastering or painting work it protects facades and walls from paint splashes. The masking foil is tear-resistant.

No traces are left behind, with excellent residue-free removal for up to 10 days outdoors. Achieve excellent and high-quality results with tesa® Easy Cover Outdoor.

Product Features

- Ideal for high-quality outdoor applications: Protects surfaces from paint splashes when doing painting works, perfect for plastering
- 2 in 1: Cloth tape and masking foil covering and masking combined
- Durable: Resists UV-sunlight for up to 10 days
- Suitable for paints, lacquers, and glazes
- Residue-free removal for up to 10 days

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of adhesive natural rubber
Total thickness 260 μm

Properties/Performance Values

•	Tensile strength	55 N/cm	•	Hazard material	no
•	Applicationfield	Garden, Home,	•	Humidity resistance	yes
		Garage	•	Material	LDPE (Low-density
•	Area of use	Outdoor			polyethylene)
•	Batteries included	no	•	Residue-free removable after	10 days
•	Batteries required	no		days	



tesa® Easy Cover Outdoor

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

