



51788 Black Plus

Product Information



Multifunctional splicing tape with integrated optical detection feature

Descripción del producto

tesa® 51788 EasySplice Black Plus is a double-sided integrated flying splice tape consisting of a flat-back paper and an acrylic adhesive.

Colour: Black

Características

- Very high tack properties
- Very high shear resistance
- Extremely good heat resistance
- Best adhesion on coated and uncoated paper
- Smooth and easy application due to a flexible backing
- Low splice thickness
- Reliable detection of splice position
- Slit liner for the secure fixation of the top sheet is included
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- One splitting strip with paper backing for a smooth opening of the new paper reel without jeopardising the printing process
- Black backing for a reliable optical detection of the splice position

Aplicación

tesa® 51788 EasySplice Black Plus is particularly suitable for:

- Flying splices in web printing industry

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------|---------|-------|
| • Material de soporte | papel liso | • Color | negro |
| • Espesor total | 110 µm | | |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|---------|----------------------|-----------|
| • Elongación a la ruptura | 7 % | • Caducidad (envase) | 18 months |
| • Resistencia a la rotura | 29 N/cm | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51788>



51788 Black Plus

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51788>