



tesa® 4309 PV1



Product Information

Cinta de enmascar de alta performance - 120°

Descripción del producto

tesa® 4309 es una cinta de enmascarado de papel finamente crepado para pintura y secado al horno hasta 120 °C

Sustainable Aspects

53% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Características

- The excellent adhesion of fillers or paints (water- or solvent-borne) to the reverse side of the tape prevents any kind of paint flaking.
- After the oven drying process with temperatures up to 120° C, tesa® 4309 can be easily removed without tearing and without leaving any residues.
- The flexible masking tape is resistant to wet sanding and features excellent adhesion to various surfaces

Aplicación

- tesa® 4309 is ideal for demanding masking tasks
- The masking tape can be used with various surfaces like metal, rubber, glass, and plastic
- The high-temperature masking tape can be used for oven-drying
- The tape is hand-tearable
- The tape offers excellent paint anchorage on reverse side

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado | • De base biológica (por peso) | 53 % |
| • Tipo de adhesivo | caucho natural | • Espesor total | 170 µm |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 12 % | • Fácil de quitar | si |
| • Resistencia a la rotura | 47 N/cm | • Hand tearability | very good |

For latest information on this product please visit <http://l.tesa.com/?ip=04309>



tesa[®] 4309 PV1

Product Information

Adhesión a los valores

- Adhesión sobre acero 3.5 N/cm

Additional Information

El producto es resistente al chorreado en mojado y tanto las pinturas como las masillas tienen muy buena adhesión, evitando descascarilleado.

Después del secado en horno hasta 120 °C se puede eliminar sin residuos.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04309>