



51913 PV11



Product Information

Cinta doble faz repulpable

Descripción del producto

tesa® 51913 es una cinta doble faz delgada, repulpable con protector. Consiste en un soporte de papel tissue y adhesivo acrílico modificado soluble en agua.

tesa® 51913 se caracteriza por:

- Muy buena adhesión en papel esmaltado y no esmaltado
- Muy bajo espesor de empalme
- Muy alta resistencia al calor
- Buen tack
- Excelente repulpabilidad sobre un rango alto de pH (pH3 - pH9)

Color: Azul, transparente.

Características

- Very high shear strength
- Very high heat resistance
- Very good adhesion values on most paper grades
- tesa® CaRes 51913 is certified by independent laboratories for: Repulpability according to TAPPI UM-213 over full pH-range (pH3 – pH9)
- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO₃)

Aplicación

tesa® 51913 es adecuada para:

- Empalmes solapados permanentes
- Empalmes al vuelo en calandras
- Inicio de bobina

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------------------------------|-----------------|-------|
| • Material de soporte | fibra sin tejer | • Espesor total | 65 µm |
| • Tipo de adhesivo | acrílico taquificado
repulpable | • Color | azul |
| • Tipo de protector | papel siliconado
repulpable | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51913>



51913 PV11

Product Information

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|-----------|--------|--------|
| • Caducidad (envase) | 12 months | • Tack | medium |
| • Resistencia al cortante | very good | | |

Additional Information

Other products for permanent overlapped splicing:

- tesa® 51912 - better bonding on heavier paper grades

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51913>