



tesa® 51916

Product Information



Repulpable transfer splicing tape

Descripción del producto

tesa® 51916 is a very thin double-sided repulpable transfer tape consisting of a modified water soluble acrylic adhesive.

Color: Blue, Colorless

Características

- Very high shear strength
- Very good adhesion on coated and uncoated paper
- Very high heat resistance
- Very low splice thickness
- Good repulpability over full pH-range (pH3 –pH9)

Aplicación

tesa® 51916 is particularly suitable for

- Permanent overlapped splices
- The use in hand dispensers or automatic applying processes
- Splicing of carbonless paper

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------------------------------|---------------------|---------------------|
| • Material de soporte | ninguno | • Tipo de protector | papel siliconado |
| • Tipo de adhesivo | acrílico taquificado
repulpable | • Espesor total | repulpable
50 µm |

Propiedades / Valores de rendimiento

- | | | | |
|---------------------------|-----------|--------|--------------|
| • Caducidad (envase) | 12 months | • Tack | good, medium |
| • Resistencia al cortante | very good | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51916>



tesa[®] 51916

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51916>