



# tesa<sup>®</sup> 4330

## Product Information



Cinta de enmascar de alta performance - 140°

### Descripción del producto

tesa<sup>®</sup> 4330 es una cinta de enmascarado de papel finamente crepado, flexible y resistente al pintado en húmedo con una resistencia a rotura elevada.

### Sustainable Aspects

48% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

### Características

- tesa<sup>®</sup> 4330 is a fine crepe paper masking tape combined with a high adhesion and temperature resistant natural rubber adhesive.
- It is the ideal solution for high demanding automotive paint jobs (water- or solvent based paints) with subsequent oven-drying up to 140°C.
- The natural rubber adhesive provides high tack and high adhesion and to a variety of surfaces like paint, metal, glass, rubber and plastic.
- Paint and filler systems adhere excellent to the reverse side avoiding any kind of flaking.
- The fine crepe paper backing has an excellent conformability and enables good cornering.

### Aplicación

- ideal for the high requirements in automotive paint jobs
- excellent adhesion to a variety surfaces like paint, metal, glass, rubber and plastic
- the conformable tape enables excellent cornering and paint / filler anchorage on reverse side
- also suited for masking of circuit boards before plating

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |                |                                |        |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado  | • De base biológica (por peso) | 48 %   |
| • Tipo de adhesivo    | caucho natural | • Espesor total                | 175 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04330>



# tesa<sup>®</sup> 4330

## Product Information

### Propiedades / Valores de rendimiento

- |                           |         |                    |           |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 12 %    | • Fácil de quitar  | si        |
| • Resistencia a la rotura | 42 N/cm | • Hand tearability | very good |

### Adhesión a los valores

- Adhesión sobre acero 4.8 N/cm

### Additional Information

La cinta garantiza líneas claras debido a su estructura finamente crepada. La adhesión de la pintura y las masillas sobre el reverso es excelente.

tesa<sup>®</sup> 4330 se puede remover fácilmente sin romepirse ni dejar restos.

tesa<sup>®</sup> 4330 está también disponible para troquelar con liner (tesa<sup>®</sup> 4330 PV1)

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04330>