



# tesa® 4163 Soft PVC



## Product Information

cinta de PVC Soft multiproposito

### Descripción del producto

tesaflex® 4163 es una cinta multipropósito de PVC blando y con buena flexibilidad. Su adhesivo acrílico estable y resistente a los rayos UV, la hace especialmente apropiada para aplicaciones permanentes. Se utiliza prioritariamente en trabajos de instalación, reparación, marcación de pisos, empalmes y amarres.

Está disponible en color negro y amarillo.

### Características

- Flame retardant according to UL510 and DIN EN 60454-2 (VDE 0340-2):2008-05, clause 20
- Flexible soft PVC backing for excellent conformability
- Good adhesion to a wide variety of surfaces
- tesa® 4163 conforms to US safety standard 302

### Aplicación

- The premium multipurpose soft PVC Tape is suitable for electric installation work, repairing, splicing, or bundling
- Available in multiple bright colors, tesa® 4163 can also be used for marking and color-coding
- Isogenogrey color for installation of e.g. water or heating pipes

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |            |                 |        |
|-----------------------|------------|-----------------|--------|
| • Material de soporte | PVC blando | • Espesor total | 126 µm |
| • Tipo de adhesivo    | acrílico   |                 |        |

### Propiedades / Valores de rendimiento

- |                           |         |                                  |        |
|---------------------------|---------|----------------------------------|--------|
| • Elongación a la ruptura | 295 %   | • Tensión de ruptura dieléctrica | 7000 V |
| • Resistencia a la rotura | 30 N/cm |                                  |        |

### Adhesión a los valores

- |                        |          |
|------------------------|----------|
| • Adhesión sobre acero | 1.8 N/cm |
|------------------------|----------|



# tesa<sup>®</sup> 4163 Soft PVC

Product Information

## Additional Information

tesa<sup>®</sup> 4163 conforms to US safety standard 302.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04163>