

51444 PV11

Product Information

Repulpable single-sided splicing tape

Descripción del producto

tesa® CaRes 51444 is a single-sided repulpable splicing tape with a liner consisting of a flat-back paper and a modified water soluble acrylic adhesive.

Características

- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO3)
- · Very thin but strong backing to allow an especially low total splice thickness
- · Printable and coatable backing for easy further processing
- · Very high shear strength
- · Very high heat resistance
- · Very good adhesion values on most paper grades
- tesa® CaRes 51444 is certified by independent laboratories for: Repulpability according to TAPPI UM-213 over full pH-range (pH3 pH9)
- Paper from well-managed certified forests and other controlled sources

Aplicación

tesa® 51444 is particularly suitable for:

- · Manual permanent butt splicing
- Use in automatic butt-splice applicators
- · Security tape

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

Material de soporte papel liso Espesor total 50 μm
Tipo de adhesivo acrílico taquificado repulpable

Tipo de protector papel siliconado

repulpable



51444 PV11

Product Information

Propiedades / Valores de rendimiento

• Elongación a la ruptura

6 %

Caducidad (envase)

12 months

Resistencia a la rotura

10 N/cm

(transversal)

Resistencia al cortante very goodTack medium

Additional Information

Other products for butt-splicing:

- tesa® 51445 stronger backing for higher splice security
- tesa® 51455 slit liner for easier manual splice application
- tesa® 51465 slit liner and splitting strip for secure tape fixation during the manual splice preparation
- tesa® 61445 black backing for optical detection

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

