



# tesa<sup>®</sup> Powerstrips Self-Adhesive Hook Rack

## Product Information

BNR 58094, 58095

## Product Description

This removable plastic hook rack by tesa is a versatile bathroom and kitchen hook rack with strong holding power.

## Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 3kg
- Removable without trace thanks to the Powerstrips<sup>®</sup> technology
- Usable on tiles, glass, wood, plastic and variety other surfaces
- Hook rack reusable with tesa Powerstrips<sup>®</sup> Large
- Completely covered tesa Powerstrips<sup>®</sup>
- Not suitable for use on styrofoam, foamed material, surfaces with non-sticking, porous material

## Application Fields

- How to apply - Step by step:
1. Clean the surface with alcohol or silicone-free glass cleaner
  2. Apply two Powerstrips Large strips horizontally to the surface keeping a distance of 80 mm between the two strips - press for 5 seconds minimum
  3. Disengage the base plate from the hook rack and stick it onto the strips - press for 5 seconds minimum
  4. Let the hook rack slide down on the base plate until it is locked.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                       |                  |                 |             |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive    | synthetic rubber | • Hook shape    | Rectangular |
| • Holding power up to | 3 Kg             | • Silicone free | yes         |



# tesa® Powerstrips Self-Adhesive Hook Rack

## Product Information

### Properties/Performance Values

• Application temperature from	+15 °C	• Residue-free removability	yes
• Application temperature to	+35 °C	• Reusable	yes
• Applicationfield	Bathroom, Kitchen	• Reusable with	Powerstrips Large
• Area of use	Indoor	• Solvent free	yes
• Batteries included	no	• Suitable surfaces	Glazed Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics, Metal
• Batteries required	no	• Temperature resistance	yes
• Chemical Resistance	no	• Temperature resistance max.	35 °C
• Hazard material	no	• Temperature resistance min.	15 °C
• Humidity sealing	no	• UV resistant	no
• Material	PS (polystyrene)	• Water resistance	no
• Oil and grease resistance	no	• Waterproof	no
• Ozone resistance	no		

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>