



tesa® Professional 4392

Product Information

Car masking film - masking and protecting of car bodies before filler and paint jobs

Product Description

tesa® Easy Protect Premium 4392 has been developed for superior paint and filler jobs. The product prevents from inconvenient spotting on the car body after oven - or IR drying at slight residual moisture. The film on the 150m roll at a width of 4m allows easy application by only one person. The print of the film and the easy measuring guide (every 50 cm) facilitate the utilization.

Product Features

- The excellent electrostatic charge secures a better adherence of the film to surface.
- Outstanding paint and filler adherence enable brilliant results.

Application Fields

- Professional lacquering work * Protection of car body * Avoids spotting at slight residual moisture

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Backing PE film

Properties/Performance Values

- | | | | |
|--------------------|----------|---------------------------------|-------|
| • Tensile strength | 6.9 N/cm | • Material of masking coverage | HDPE |
| • Easy to remove | yes | • Thickness of masking coverage | 16 µm |



tesa[®] Professional 4392

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04392>