



**Product Information** 



Paper-based reinforcement tape

## Deskripsi Produk

Paper-based reinforcement tape

#### **Sustainable Aspects**



### **Product Features**

- strong, paper-based backing
- reliable adhesive that offers strong bond to commonly used carboard materials
- tape can be disposed and recycled along with box mateiral
- no need to be separated during repulping process

#### Penerapan

- for reinforcement of lightweight and thinner flute packaging
- designed to be used for adding strength to critical areas, e.g. carry-handles or side hole handles

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Konstruksi Produk

| <ul><li>Backing</li><li>Type of adhesive</li></ul> | Paper<br>synthetic rubber | • | Total thickness<br>Color  | 220 μm<br>brown |
|--|---------------------------|---|---------------------------|-----------------|
| Berbagai macam produk                              |                           |   |                           |                 |
| Available colors                                   | brown                     |   |                           |                 |
| Properti / Nilai Kinerja                           |                           |   |                           |                 |
| <ul> <li>Elongation at break</li> </ul>            | 12 %                      | • | No discoloration          | no              |
| Tensile strength                                   | 145 N/cm                  | • | Residue-free removability | no              |
| Adhesi pada Nilai                                  |                           |   |                           |                 |
| • Steel  | 11 N/cm                   |   |                           |                 |





**Product Information** 

# **Additional Information**

Paper-based reinforcement tape

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=51345