



# tesa® 51230 PV1



## 제품 정보

21230 PV1

## 제품 설명

tesa® 51230 PV1 is a self-adhesive tensilised polypropylene tear strip with a synthetic rubber adhesive system.

Due to a co-extruded PP/PE backing tesa® 51230 PV1 exhibits an excellent and unique tear performance despite its relatively low thickness.

The product is recommended for high unwinding speeds in automatic production.

## 특징:

- \* excellent tack
- \* excellent adhesion and shear resistance on a variety of corrugated and solid cardboard surfaces
- \* robust backing

## 특성

- Excellent tack
- Excellent adhesion and shear resistance on a variety of corrugated and solid cardboard surfaces
- Robust backing
- Due to a co-extruded PP/PE backing tesa® 51230 PV1 exhibits an excellent and unique tear performance despite its relatively low thickness.

## Applications

- for medium grades of solid board and double-wall corrugated cardboard
- \* use on detergent and consumer cartons, padded shipping envelopes, express delivery and courier envelopes

## Technical Information (average values)

The values in this section should be considered representative or typical only

관련제품 최신자료는 다음의 경로를 클릭하세요 <http://l.tesa.com/?ip=51230>



# tesa® 51230 PV1

## 제품 정보

### Technical Information (average values)

and should not be used for specification purposes.

### 제품 구조

• 기재 소재	MOPP	• 총두께	90 µm
• 점착제 종류	합성고무		

### 속성 / 성능 값

• 연신률	25 %	• 인장강도	165 N/cm
-------	------	--------	----------

### 점착력(수치)

• Steel점착력	5.5 N/cm
------------	----------

## 공지사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다



관련제품 최신자료는 다음의 경로를 클릭하세요 <http://l.tesa.com/?ip=51230>