



# tesa® 51917

## Product Information



Vannoppløselig, dobbeltklebende skjøtetape

### Produktbeskrivelse

tesa® 51917 er en dobbeltsidig resirkulerbar tape, som består av silkepapir og et modifisert vannoppløselig akrylklebestoff.

tesa® 51917 viktige egenskaper

- De beste klebeegenskaper
- Kleber veldig godt til bestrøket og ubestrøket papir
- God skjærefasthet
- Gode resirkuleringsegenskaper i full pH-område (pH3-pH9)

Farge: Blå, fargeløs

### Funksjoner

- Highest tack properties
- Very good adhesion values on coated and uncoated papers
- Good shear strength
- Good repulpability over full pH-range (pH3 –pH9)

### Applikasjon

tesa® 51917 passer spesielt til

- Flygende skjøteprosesser med kritiske klebeforhold

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |                                 |                  |                        |
|-----------------|---------------------------------|------------------|------------------------|
| • Bæremateriale | Non-woven                       | • Type liner     | repulpable siliconised |
| • Klebetype     | repulpable tackified<br>acrylic | • Total tykkelse | paper<br>115 µm        |

### Egenskaper / ytelsesverdier

- |                                  |           |                           |              |
|----------------------------------|-----------|---------------------------|--------------|
| • Klebeevne                      | very good | • Statisk strekkholdkraft | good, medium |
| • Lagringstid (emballert) < 25°C | 12 months |                           |              |



# tesa<sup>®</sup> 51917

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51917>